

## Low Maintenance Laser Lightsource for Constant Brightness Level and Color Performance for up to 20,000 hours

The DU3661Z laser projector will appeal to any business owner, and is of equal interest to System Integrators looking for compact laser projectors for simulation or display projects. Compact in size and weighing only 7kg, the DU3661Z offers 5,000 Lumens of brightness and WUXGA resolution to deliver the high performance. The projector comes with smart features to facilitate meetings and to increase productivity before, during and after its use. In addition, the model come with three HDMI ports, HDBaseT, flexible installation features for easy set up.



## DU3661Z SPECIFICATIONS

Imaga		
Image	Display Type	Single chip DLP® Technology by Texas Instruments
	Brightness	5000 ANSI Lumens
	Native Resolution	WUXGA (1920 x 1200)
	Max. Supported Resolution	WUXGA (1920 x 1200) @60Hz
	Contrast Ratio	2000000:1
	Native Aspect Ratio	16:10
	Keystone Correction	Vertical: +/-30 Steps; Horizontal: +/-30 Steps
Optical	Throw Ratio	1.39 - 2.09 : 1
	Projection Lens	F = 2.42 - 2.97, f = 20.7 - 31.05 mm
	Zoom Ratio	1.5x
	Offset	108.5% - 120.2% with Manual Lens Shift
	Lens Shift Range	Vertical: +11.7%
Features	Features	3D Ready(DLP link, PC+Video), Direct 3D (HDMI 1.4a), 3D Mandatory Formats supported (top/bottom, right/left, frame sequential), Keypad lock
Compatibility	Video	SDTV (480i, 576i) / EDTV (480p, 576p) / HDTV (720p, 1080i, 1080p), NTSC (M, 3.58/4.43 MHz), PAL (B,D,G,H,I,M,N) SECAM (B,D,G,K,K1,L)
Connectivity	I/O Connection Ports	VGA-In (15pin D-Sub), HDMI Number of Ports v.1.4 (x3), Composite Video, Audio-In (RCA), Audio-In (Mini-Jack), VGA-Out (15pin D-Sub), Audio-Out (Mini-Jack), RJ45 (x2: HDBaseTx1, LANx1), RS-232, USB A (Power Only), USB miniB (Service), Microphone (Mini-Jack)
General	Lamp Life and Type	Lamp free design. Laser light source lasts up to 20,000 hours
	Speakers	10W x 1
	Dimensions (W x D x H)	395 x 341 x 136 mm
	Weight	7 kg
	Weight Noise Level	7 kg 35dB / 29dB (Normal / Eco. Mode)
		5
	Noise Level	35dB / 29dB (Normal / Eco. Mode) Supply: AC 100-240V, 50/60Hz. Consumption: 270W (Eco. Mode), 340W
	Noise Level Power	35dB / 29dB (Normal / Eco. Mode) Supply: AC 100-240V, 50/60Hz. Consumption: 270W (Eco. Mode), 340W (Normal Mode), <0.5W (Standby) PJ- Control V3.0.0.4 Standard Laser Phosphor Projector Warranty: 5-Year warranty on projector/
	Noise Level Power Control Software	35dB / 29dB (Normal / Eco. Mode) Supply: AC 100-240V, 50/60Hz. Consumption: 270W (Eco. Mode), 340W (Normal Mode), <0.5W (Standby) PJ- Control V3.0.0.4 Standard Laser Phosphor Projector Warranty: 5-Year warranty on projector/ year or 10000h on the Laser Phosphor illumination source (whichever come

 $\ensuremath{\mathbb{C}}$  Copyright 2022 Vivitek. Vivitek is a registered trademark of Delta Electronics, Inc.

DLP® and the DLP logo are registered trademarks of Texas Instruments. All specifications are subject to change at any time.

Vivitek EMEA, Zandsteen 15, 2132 MZ Hoofddorp, The Netherlands. Tel: + tel: +31 20-8003960 | fax: +31 20-8003999 | email: info@vivitek.eu